


**Conductivity and Permeability of the Submitted
70/140 V8 Stikine Sand Sample (Duplicate Testing)
At 2 lb/ft² and at 150°F for 50 Hours at Each Closure
Stress of 2,000 - 8,000 psi between Ohio Sandstone**

Prepared For:

Mr. Scott Broughton
Stikine Gold Corporation
1122 Mainland St., #490
Vancouver, BC V6B 5L1
Canada

Prepared By:

Stim-Lab, Inc.
P.O. Box 1644
7406 North Hwy 81
Duncan, OK 73534-1644



Kathy Abney, Conductivity Supervisor

P.O. Number: Verbal to Lisa O'Connell
From Scott Broughton

File Number: SL 8862 Cond

July 2010

ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM SAMPLES AND LOGS, WHICH WERE SUPPLIED. WE CANNOT, AND DO NOT, GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATIONS, AND WE SHALL NOT, EXCEPT IN THE CASE OF GROSS OR WILLFUL NEGLIGENCE ON OUR PART, BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COSTS, DAMAGES OR EXPENSES INCURRED OR SUSTAINED BY ANYONE RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR OFFICERS, AGENTS OR EMPLOYEES. THESE INTERPRETATIONS ARE ALSO SUBJECT TO OUR GENERAL TERMS AND CONDITIONS AS SET OUT IN OUR CURRENT PRICE SCHEDULE. **NOTICE: SAMPLES SUBMITTED TO STIM-LAB, INC. FOR USE IN TESTING SERVICES ARE SUBJECT TO DISPOSAL OR STORAGE FEES FOLLOWING THE COMPLETION OF THE TESTING SERVICES.** DIRECTIVE AS TO THE DISPOSITION OF SAMPLES MUST BE SUBMITTED IN WRITING WITH THE SAMPLES OR OTHERWISE PROVIDED DURING THE COURSE OF THE PROJECT. STIM-LAB, INC. RESERVES THE RIGHT TO REQUEST THAT YOU PICKUP SAMPLES, WHETHER FORMATION MATERIAL, CHEMICALS SUPPLIED, FIXTURES OR OTHER MATERIALS RELATING TO A PROJECT. YOU MAY BE CHARGED A REASONABLE SHIPPING AND PACKAGING FEE FOR RETURN OF SAMPLES FOR WHICH PICK UP ARRANGEMENTS HAVE NOT BEEN MADE. STIM-LAB, INC. EXPRESSLY DISCLAIMS LIABILITY FOR INTENTIONAL DISPOSAL OR UNINTENTIONAL LOSS OF SUBMITTED SAMPLES FOR WHICH NO WRITTEN DIRECTIVE HAS BEEN PROVIDED.



STIM-LAB, Inc.
7406 North HWY 81
Duncan, Oklahoma 73533
Phone: 580-252-4309
Fax: 580-252-6979
Kathy.Abney@corelab.com

Kathy Abney
Conductivity Supervisor

July 8, 2010

Mr. Scott Broughton
Stikine Gold Corporation
1122 Mainland St. #490
Vancouver, BC V6B 5L1
Canada

Dear Mr. Broughton;

Stim-Lab, Inc. has completed the duplicate evaluations of the long-term conductivity on the submitted sample labeled 70/140 V8 Stikine sand product. The sample was delivered to Stim-Lab on April 28, 2010. The sample was evaluated in duplicate at 2.0 lb/ft² at 150°F and 2000, 4000, 6000 and 8000 psi closure stresses for 50 hours each between Ohio Sandstone. An ISO 13503-2/API RP19C crush evaluation of the sample was performed and reported in a separate report.

Figure 1 contains a summary of conductivity and permeability vs. stress. Figures 2 compares the measured conductivity of this sample with predicted values from Predict-K 10.5 using the 70/140 Stikine V8 sand sieve distribution and the one types of 70/140 frac sand in the data base. The data is presented in Tables 1 and 2. The sieve analysis of the sample is provided in Table 3. The procedures utilized are outlined in the following section of this report.

Thank you for allowing Stim-Lab to perform this test series. If you have any questions regarding the testing or results, please do not hesitate to give me a call.

Sincerely,

Kathy Abney
Conductivity Supervisor



PROCEDURE FOR CONDUCTIVITY AND LIQUID PERMEABILITY MEASUREMENTS

- 1) The equipment used for the measurement of conductivity and liquid permeability included:
 - (a) 75 ton Dake Press with air oil intensifier. API SS316 flow cells with 10 sq in. flow paths.
 - (b) Rosemont (smart family) 40:1 pressure transducers for measuring pressure drop and rate plumbed with ¼ in. lines and calibrated with the smart system computer and set at the 0-5 inch of water span range.
 - (c) Two gallon nitrogen driven fluid reservoirs filled with 2% KCl and deoxygenated with nitrogen.
 - (d) Internal gauges and calipers for measuring widths.
 - (e) IBM PC to process data and calculate conductivity and permeability.
 - (f) Two - 10 sq in. Ohio Sandstone.
2. An API cell was loaded with proppant sample to be tested. The proppant was leveled with a blade device.
3. The proppant sample was placed between the core slabs and was made a part of a two-cell stack.
4. The cells were stacked to within 0.002 in. from top to bottom and positioned between the platens of the Dake Press. Pressure was increased to 500 psi and the system was evacuated and saturated with water at 70-75 °F.
5. Once saturated, the closure pressure was increased to 1,000 psi, at a rate of 100 psi/min. The proppant was allowed to equilibrate as outlined in the data tables.
6. The flow rate, pressure differential, and average width were measured at each pressure in order to calculate conductivity and permeability. Five measurements were taken and averaged to arrive at each conductivity. Flow rate was measured with a LiquiFlow meter, which was calibrated with a balance to 0.01 ml/min. Darcy's Law was used for the calculations to determine the conductivity and permeability.
7. The test temperature was increased to 150 °F and allowed to equilibrate. The temperature was left at 150 °F for 12 hours prior to increasing the closure.
8. The conductivity and permeability of the proppant were collected at 1,000 psi at both room temperature and 150 °F as stated in the data tables.
9. The pressure was increased at 100 psi per minute at 1,000 psi increments and the above measuring technique repeated.

10. The conductivity and permeability of the proppant were continuously monitored at 2,000 psi and 150 °F for 50 hours.
11. The conductivity and permeability of the proppant were continuously monitored at 4,000 psi and 150 °F for 50 hours.
12. The conductivity and permeability of the proppant were continuously monitored at 6,000 psi and 150 °F for 50 hours.
13. The conductivity and permeability of the proppant were continuously monitored at 8,000 psi and 150 °F for 50 hours.

All ISO13503-2:2006 / API RP-19C evaluations followed the procedures as outlined in this document. These procedures were created from the old API RP 56, 58 and 60 procedures which were rolled into one new procedure which was published in 2006. The specifications were published in 2008 in a separate document.